

DH-IPC-HDW1439V-PV

4MP Entry Smart Dual Light Active Deterrence Fixed-focal Eyeball Network Camera



Series Overview

With features of simple installation, easy operation, and high performance-cost ratio, Dahua Entry series network camera is applicable to small and medium-sized scenes, such as homes/residences, small-sized retail stores, and other small and medium-sized enterprises.

Functions

Siren and Light Active Deterrence

Dahua siren and light active deterrence network camera supports the light alarm and voice alarm when perimeter event occurs, to realize the deterrence and effective intervention. The camera is built in multiple voices for selection, and supports customized voice importing.

Smart Dual Light

Dahua Smart Dual Light technology adopts smart algorithm to detect targets. Usually, the IR illuminator is on at night; when the target appears in the monitoring area, the white light is on, and the camera records the full-color video and information of key events. That is, the camera links snapshot and video with full-color image. When the target is out of the monitoring area, the white light is off and the IR illuminator is on, which reduces light pollution efficiently.

Human Detection

Dahua intelligent algorithms extract moving human targets from videos and filters out alarms that are triggered by non-human targets to increase the accuracy and effectiveness of alarms.

Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, Dahua smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

- 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image.
- · Outputs max. 4 MP (2560 × 1440)@25/30 fps.
- · H.265 codec, high compression rate, ultra-low bit rate.
- Built-in IR LED and warm light, and the max. IR distance is 30 m, the max. warm light distance is 30 m.
- WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments.
- Abnormality detection: Motion detection, video tampering, audio detection, network disconnection, IP conflict and illegal access.
- · Built-in Mic; built-in speaker; support two-way talk.
- 12 VDC/PoE power supply, easy for installation.
- · IP67 protection.
- · Sound and light alarm.
- · Supports human detection.
- · One-tap arming/disarming.













Protection (IP67, Wide Voltage)

IP67: The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can work normally after soaking in 1 m deep water for 30 minutes.

Wide voltage: The camera allows $\pm 30\%$ (for some power supplies) input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

	Technical Specification							Smart Codec	Smart H.265+; Smart H.264+
Max. Resolution	Camera								- , , , ,
Max. Resolution 250 (16) × 140 (17)	Image Sensor		1/2.9" CMOS				Video Frame Rate	Video Franco Bata	
28 No 128 No 1	Max. Resolution		2560 (H) × 1440 (V)						
Same 12 18 18 18 18 18 18 18	ROM		128 MB						subjected to the total encoding capacity.
Second System	RAM		128 MB					Streaming Capability	2 streams
Main	Scanning System		Progressive					Resolution	1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 ×
Mon.	Electronic Shutter Speed		Auto/Manual 1/3 s-1/100,000 s						
Video INI Rate	Min. Illumination		0.0006 lux@F1.6 (B/W, 30 IRE)					Bit Rate Control	CBR/VBR
	S/N Patio							Video Bit Rate	
								Day/Night	Auto(ICR)/Color/B/W
	Illumination Distance							BLC	Yes
Angle Adjustment Pan : 0 -3 60° White Balance Auto, natural; street lamp; outdoor; manual; regional custom Castom Castom	Illuminator On/Off Control		Auto;Manual					HLC	Yes
Angle Adjustment File: 0 - 360° Lens Lens Lens Type	Illuminator Number		1 (IR LED); 1 (Warm light)					WDR	120 dB
Lens Type Fixed-fixed Manual-Judro Manual-Judro Manual-Judro Motion Detection Motion Detection Motion Detection OFF/ON (4 areas, rectangular)	Angle Adjustment		Tilt: 0°-78°					White Balance	• • • • • • • • • • • • • • • • • • • •
Noise Reduction SD NR			κοταποη: 0°–360°					Gain Control	Manual;Auto
Motion Detection OFF/ON (4 areas, rectangular)								Noise Reduction	3D NR
Region of Interest (Rol) Yes (4 areas)								Motion Detection	OFF/ON (4 areas, rectangular)
Max. Aperture File File File File File Smart Illumination Yes Find Yes Find Yes Find Yes Find Fixed Fix								Region of Interest (RoI)	Yes (4 areas)
Smart Dual Light Yes Smart Dual Light Image Rotation O'/180° Yes Smart Dual Light	-							Smart Illumination	Yes
Iris Control Fixed Fixed Fixed Mirror Mir	Max. Aperture							Smart Dual Light	Yes
Close Focus Distance 2.8 mm: 1.1 m (3.61 ft) 3.6 mm: 1.5 m (4.92 ft) Lens Detect Distance 2.8 mm 64.0 m (209.97 ft) (83.99 ft) (41.99 ft) (70.99 ft) DORI DORI Distance *DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances, refer to installation and commissioning manual/project design tool. Intelligence Human Detection Support the classification and accurate detection of human Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos Video Video Video Video Lens Detect Dosrve Recognize Identify Identify Audio Built-in MIC Yes, built-in Mic Built-in MIC Yes, built-in Mic Audio Compression G.711a; G.711Mu; PCM; G.726 Alarm Alarm Network disconnection; IP conflict; illegal access; motion detection; video tampering; audio detection ; SMD (human); security exception; Network Network Network Network Port RJ-45 (10/100 Base-T) SDK and API Yes Intelligent search, event extraction and merging to event videos Video Video Video Video Video Video Video Audio Built-in MIC Yes, built-in Mic Built-in MIC Audio Compression G.711a; G.711Mu; PCM; G.726 Alarm Network disconnection; IP conflict; illegal access; motion detection; iSMD (human); security exception; Network Network Network RJ-45 (10/100 Base-T) SDK and API Yes Interperability ONVIF (Profile S. & Profile T); CGI Video Audio Built-in MIC Ves, built-in Mic Audio Built-in MIC Network disconnection; IP conflict; illegal access; motion detection; iP conflict; illegal access; motion detection; iP conflict; illegal access; motion d	Field of View							Image Rotation	0°/180°
Lens Detect Observe Recognize Identify 2.8 mm (64.0 m (209.97 ft) (83.99 ft) (41.99 ft) (20.99 ft) 3.6 mm (255.91 ft) (102.36 ft) (51.18 ft) (25.59 ft) DORI Distance *DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool. Intelligence Human Detection Support the classification and accurate detection of human Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos Work together, with Smart NVR to perform refine intelligent search, event extraction and merging to event videos Wideo User/Host 6 (Total bandwidth: 24 M) Wideo Audio Audio Built-in MIC Yes, built-in Mic Built-in MIC Audio Compression A. Audio Compression A. Audio Compression A. Audio Compression Built-in MIC Audio Compression A. Audio Compresi	Iris Control		Fixed					Mirror	Yes
Lens Detect Observe Recognize Identify 2.8 mm 64.0 m (29.97 ft) (83.99 ft) (41.99 ft) (20.99 ft) 3.6 mm 78.0 m (255.91 ft) (102.36 ft) (51.18 ft) (25.59 ft) DORI Distance *DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function and commissioning manual/project design tool. Intelligence Human Detection Support the classification and accurate detection of human Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos Wideo H 265 H 264 H 264H H 264B MIPEG (Only supported) Built-in MIC Yes, built-in MIC Yes Alarm Network disconnection; IP conflict; illegal access; motion detection; iP conflict; illeg	Close Focus Distance		· · ·					Privacy Masking	4 areas
2.8 mm 64.0 m (20.99 ft) (83.99 ft) (41.99 ft) (20.99 ft) 3.6 mm 78.0 m (255.91 ft) (102.36 ft) (151.8 ft) (25.59 ft) (102.36 ft) (152.36 ft) (152.		Lens				Identify		Audio	
2.8 mm (209.97 ft) (83.99 ft) (41.99 ft) (20.99 ft) (20		ECIIS	64.0 m	25.6 m	12.8 m	6.4 m		Built-in MIC	Yes, built-in Mic
DORI Distance *DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool. Intelligence Human Detection Support the classification and accurate detection of human Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos Video H 265: H 264: H 264: H 264: H 2648: MIPEG (Only supported) Alarm Alarm Network disconnection; IP conflict; illegal access; motion detection; video tampering; audio detection ;SMD (human); security exception; Network Network Network Port SDK and API Yes Interoperability Network Protocol Interoperability ONVIF (Profile S & Profile T); CGI Video User/Host 6 (Total bandwidth: 24 M)		2.8 mm						Built-in Speaker	Yes, built-in speaker
Distance *DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool. Intelligence Human Detection Support the classification and accurate detection of human Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos Higher to the province of the province o		3.6 mm						Audio Compression	G.711a; G.711Mu; PCM; G.726
(EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool. Intelligence Human Detection Support the classification and accurate detection of human Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos Wideo H 265: H 264: H 264B: MIPEG (Only supported) Alarm Event Network Alarm Event Network disconnection; IP conflict; illegal access; motion detection; video tampering; audio detection ;SMD (human); security exception; Network Network Network Network Port SDK and API Yes Network Protocol Interoperability ONVIF (Profile S & Profile T); CGI Video		*DODI /Datas						Alarm	
distances. For intelligent function distances, refer to installation and commissioning manual/project design tool. Intelligence Human Detection Support the classification and accurate detection of human Metwork Port SDK and API Yes IPv4; IPv6; HTTP; TCP; UDP; ARP; RTSP; RTSP; RTCP; RTMP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP; P2P; Auto Registration Interoperability Video User/Host 6 (Total bandwidth: 24 M)	Distance	(EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation						Alarm Event	motion detection; video tampering; audio detection
Intelligence Human Detection Support the classification and accurate detection of human Metwork Port SDK and API Yes IPv4; IPv6; HTTP; TCP; UDP; ARP; RTSP; RTSP; RTCP; RTMP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP; IGMP; P2P; Auto Registration Video Video H 265: H 264: H 264B: MIPEG (Only supported) View Support the classification and accurate detection of human IPv4; IPv6; HTTP; TCP; UDP; ARP; RTSP; RTSP; RTCP; RTMP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP; IGMP; P2P; Auto Registration Interoperability ONVIF (Profile S & Profile T); CGI Video								Network	
Human Detection Support the classification and accurate detection of human Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos Wideo Smart Search SDK and API Yes IPv4; IPv6; HTTP; TCP; UDP; ARP; RTSP; RTCP; RTMP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP; P2P; Auto Registration Interoperability ONVIF (Profile S & Profile T); CGI User/Host 6 (Total bandwidth: 24 M)						Network Port	RJ-45 (10/100 Base-T)		
Human Detection human IPv4; IPv6; HTTP; TCP; UDP; ARP; RTSP; RTSP; RTSP; RTCP; Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos Network Protocol RTMP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP; P2P; Auto Registration Interoperability ONVIF (Profile S & Profile T); CGI Video User/Host 6 (Total bandwidth: 24 M)	Support the			the classification and accurate detection of				SDK and API	Yes
event videos Interoperability ONVIF (Profile S & Profile T); CGI Video User/Host 6 (Total bandwidth: 24 M)			Work together with Smart NVR to perform refine					Network Protocol	RTMP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast;
H 265: H 264: H 264H: H 264R: MIPEG (Only supported	Smart Search							Interoperability	ONVIF (Profile S & Profile T); CGI
H 265: H 264: H 264H: H 264R: MIPEG (Only supported	Video							User/Host	6 (Total bandwidth: 24 M)
VIII THE TAXABLE TO T	Video Compression		H.265; H.264; H.264H; H.264B; MJPEG (Only supported by the sub stream)					Storage	FTP

IE; Chrome; Firefox			
Smart PSS Lite; DSS; DMSS			
iOS;Android			
Digest;WSSE;Account lockout;Security logs;Generation and importing of X.509 certification;HTTPS;Trusted boot;Trusted execution;Trusted upgrade			
CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU			
12 VDC/PoE (802.3af)			
Basic: 1.8 W (12 VDC); 2.5 W (PoE); Max.: 8.5 W (12 VDC); 10 W (PoE) (H.265 + intelligence on + WDR + IR intensity + warm light deterrence + speaker)			
No			
-40 °C to +60 °C (-40 °F to +140 °F)			
≤95% (RH), non-condensing			
-40 °C to +60 °C (-40 °F to +140 °F)			
≤95% (RH), non-condensing			
IP67			
Inner core: Metal + Plastc; Cover: Plastc			
100.9 mm × Φ109.9 mm (3.97" × Φ4.33")			
0.32 kg (0.71 lb)			
0.46 kg (1.01 lb)			

Ordering Information								
Туре	Model	Description						
IP CAMERA	DH-IPC-HDW1439V-PV	4MP Entry Smart Dual Light Active Deterrence Fixed-focal Eyeball Network Camera						
	DH-PFA109	Mount Adapter						
	DH-PFB220C	Ceiling Mount Bracket						
	DH-PFB305W	Wall Mount Bracket						
	DH-PFA151	Corner Mount Bracket						
	DH-PFA150	Pole Mount Bracket						
Accessories (Optional)	DH-PFA152-E	Pole Mount Bracket						
	DH-PFB205W-E	Wall Mount Bracket						
	DH-PFA13G	Junction Box						
	DH-PFM321-EN	DC12V1A power adapter						
	DH-PFM320D-EN	DC12V2A power adapter						
	PFM900-E	Integrated Mount Tester						

Accessories

Optional:







DH-PFA109 Mount Adapter

DH-PFA13G Junction Box

DH-PFA150 Pole Mount Bracket







DH-PFA151 Corner Mount Bracket

DH-PFA152-E Pole Mount Bracket

DH-PFB205W-E Wall Mount Bracket







DH-PFB220C Ceiling Mount Bracket

DH-PFB305W Wall Mount Bracket


DH-PFM320D-EN DC12V2A power adapter






DH-PFM321-EN DC12V1A power adapter Integrated Mount Tester







Dimensions (mm[inch])

mm [inch]

